



SMART-DRY 4 DRYING CABINET NFPA 1851 COMPLIANT

STANDARD FEATURES

- Automatic & manual programs
- Preset start time
- Temperature & humidity tracking system
- Energy-efficient
- Electric heated air drying
- Gentle drying technology without mechanical action
- Double overheat protection
- Powder coated galvanized steel
- Program ends with "cool down" mode
- Interior lighting
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Ideal for delicate and hard to dry textiles and accessories


INCLUDED ACCESSORIES

- Hanging rod
- Four Dry Kwik coat hangers
- Two ventilated shelves


OPTIONAL ACCESSORIES

 Door hook racks that attach on the inside of the door for drying additional accessories









Electrical connection
Outlet exhaust

| Dimensions in/mm | А | В | С | D | E |
|---------------------|-----------|------------|-----------|----------------------------|----------------------------|
| Smart-Dry 4 | Width | Depth | Height | Exhaust position from side | Exhaust position from back |
| Drying Cabinet | 47 / 1200 | 25.2 / 640 | 74 / 1870 | 18.5 / 469 | 9.5 / 242 |

В

TECHNICAL SPECIFICATIONS SMART-DRY 4 DRYING CABINET

| Machine Type | | Drying Cabinet |
|--|----------------|------------------------------------|
| Product Name | | Smart-Dry 4 |
| Product No. | | SDC4 |
| Main Data | | |
| Туре | | Air vented |
| Capacity, sets of turnout gear | | 4 |
| Capacity (dry weight) | lbs / kg | 22 / 10 |
| Interior capacity | cu ft / L | 34.7 / 983 |
| Drying capacity | oz/min / g/min | 2.2 / 62 |
| Energy consumption | kWh | 3.0 |
| Noise emission | dB(A) | 62 |
| Electrical Installation | | |
| Supply Voltage | V | 208-240v, 1ph, 60Hz |
| Electric heating | W | 4500 |
| Electric fan | W | 350 |
| Total effect | W | 4850 |
| Protection | А | 30 |
| Dimensions | | |
| Outer: width × depth × height | in / mm | 47 × 25.2 × 74 / 1200 × 640 × 1870 |
| Shipping: length × width × height | in / mm | 68 × 25 × 48 / 1727 × 635 × 1219 |
| Weight | | |
| Weight | lb / kg | ≈320 / ≈145 |
| Shipping weight | lb / kg | 420 / 191 |
| | , | |
| Ventilation | | |
| Outlet exhaust | Ø in / mm | 6 / 152 |
| Outlet airflow | cfm / m³/h | 135 / 230 |
| Pressure drop, max | psf / Pa | 1.46 / 70 |
| Maximum airflow (at 0% pressure) | cfm / m³/h | 200 / 340 |
| Optional Accessories | | |
| Hooks for drying cabinet door: 3 separate rows with 4 hooks on each, 1 set = 1 door | Product No. | SDDH |
| | | |

For freight cost savings, the drying cabinet ships knocked down in a crate. Assembly is required.

